



CONSTRUCTION

Sustainable, PVC Free, Breathable Proprietary Polyester/
Natural Fiber Technology

INSTALLATION

Standard commercial wallcovering pastes, primers
and techniques. For indoor use in environmentally
controlled spaces.

WEIGHT & THICKNESS

- **Product Weight:** 14oz. per lineal yard
- **Thickness:** 0.017in to 0.024in.

TYPE II PROPERTIES

Passes all criterion for WA-101 Type II
properties including:

- Break Strength
- Shrinkage
- Washability
- Tear Strength
- Stain Resistance
- Scrubability
- Cold Crack
- Coating Adhesion (Bond)
- Blocking
- Heat Aging
- Colorfastness
- Crockness

SPECIFICATIONS

Federal Specification:
CCC-408-D Type II*

WA Specification:
WA-101 , NSF/ANSI 342 Sustainability Standard

NFPA Life Safety Code 101*

FIRE RATINGS

- **ASTM-E84 Tunnel Test:** Passed Class A
- **CAN/ULC-S102** Passed all requirements

MOLD/MILDEW

- **ASTM-G21 Specs:** Passed all requirements

SUSTAINABILITY

- NSF-342 - Certified for Silver compliance
- HPD - Health Product Declaration available
- EPD - Environmental Product Declaration available
- UL third party certified for wallcovering industry
average
- Low VOC - Meets California CDPH Standard for
Schools and Offices when tested to CA 01350
- PVC & POA (Olefin) free, No Plasticizers, No Chlorine,
No Formaldehyde, No heavy metals
- Prop 65 compliant
- Manufactured without the use of Brominated flame
retardants
- Recycled Content - Minimum 31% post-consumer
recycled content

WARRANTY

5 Year Warranty against manufacturing defects.