



CONSTRUCTION

Embossed vinyl face with laminated fabric backing. Backing is poly-cotton woven or polyester/pulp non-woven depending on emboss.

INSTALLATION

Standard commercial wallcovering pastes, primers and techniques. For indoor use in environmentally controlled spaces.

WEIGHT & THICKNESS

- **Product Weight:** 20oz. per lineal yard
(13 oz. per sq yd)
- **Thickness:** 0.017in to 0.027in.

TYPE II PROPERTIES

Passes all criterion for WA-101 Type II properties including:

- Break Strength
- Shrinkage
- Washability
- Tear Strength
- Stain Resistance
- Scrubability
- Cold Crack
- Coating Adhesion (Bond)
- Blocking
- Heat Aging
- Colorfastness
- Crockness

SPECIFICATIONS

Federal Specification:
CCC-408-D Type II*

WA Specification:
WA-101 , NSF/ANSI 342 Sustainability Standard
NFPA Life Safety Code 101*

FIRE RATINGS

- **ASTM-E84 Tunnel Test:** Passed Class A
- **EU Class Flame (EN15102):** Passed Class B, s2
- **BS476 Parts 6&7** Passed all requirements
- **CAN/ULC-S102** Passed all requirements

MOLD/MILDEW

- **ASTM-G21 Specs:** Passed all requirements

SUSTAINABILITY

- NSF-342 - Certified for Silver compliance for all 20 oz wallcovering constructions
- HPD - Health Product Declaration available
- EPD - Environmental Product Declaration available - UL third party certified for wallcovering industry average
- Low VOC - Meets California CDPH Standard for Schools and Offices when tested to CA 01350
- Contributes to LEED v4
- Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde
- Phthalate free formulation
- Prop 65 compliant
- Manufactured without the use of Brominated flame retardants
- For non-woven backed constructions:
 - 11% post-consumer content in total product - using recycled polyester, cellulose
 - 100% of backing fiber content is post-consumer fiber

WARRANTY

5 Year Warranty against manufacturing defects.